

GBC® AdvancedPunch™

Expand your Xerox® Production Family with finishing options to produce a wider variety of print jobs.

The new GBC AdvancedPunch for the Xerox® Versant™ 2100 Press, Xerox® D Series Copier/Printer, Xerox® D Series Printer, Xerox® Color C75®/J75 Presses and Xerox® Color C60/C70 Printer lets you create professionally bound documents in-house by combining printing, punching and collating into one convenient step. You can select from various interchangeable die sets for popular binding styles without manual punching, thereby increasing productivity and lowering costs while producing professional looking documents.

Features

- Enables inline printing, punching and collating for ready-to-bind offline applications
- AdvancedPunch module is fully integrated with the printer
- Select from various interchangeable (optional) die sets for popular binding styles; no need for offline manual punching
- Three additional die sets can be stored within the AdvancedPunch module
- User-friendly replacement of die sets without need for levers or tools
- AdvancedPunch module uses a unique waste container sensor design and includes a large waste container to collect scrap punches
- Supports punching of pre-cut tab stock to create punched applications such as manuals, guides or planners

Benefits

- Maximize productivity and lower overall cost of production; reduce setup time and cost associated with manual finishing by providing ready-to-bind documents at the touch of a button
- Add style and versatility to bound documents; up to seven common punching styles produce ready-to-bind documents at rated speeds
- Easy to create professionally bound documents in-house for commonly used offline binding styles
- Designed for walk-up users or for production professionals, so users can initiate punch jobs right from their desktop or from the print controllers



Xerox® Versant™ 2100 Press




Xerox® D Series Copier/Printer




Xerox® D Series Printer



Xerox® Color C60/C70 Printer



Xerox® Color J75 Press



Xerox® Color C75 Press

Power Requirements

- 115 VAC
- 60 Hz/220 Volts, 50 Hz

Dimensions

- 12 in. (305 mm) Width
- 38.5 in. (978 mm) Height
- 28.5 in. (724 mm) Depth

Weight

- 154 lb (70 kg)

Paper Type

- Coated and uncoated

Paper Weights

- 20 lb Bond – 80 lb Cover, uncoated (75 – 216 gsm)
- 28 lb Bond – 80 lb Cover, coated (106 – 216 gsm)

Paper Size (min/max)






















- 8.5 x 11 in. (A4) long edge feed (11 in. side only)
- Bypass mode up to 13 x 19.2 in. (330 x 488 mm) paper

Punch Type

- Customer replaceable die sets

Note: GBC AdvancedPunch requires the Interface module and follow on finisher—High Capacity Stacker or Standard Finisher or Booklet Maker Finisher.

Die Punch Sets for Letter Size

Description	Punch Pattern	Bind Style	Recommended Finisher
19-Hole CombBind (standard with punch module) • Conventional binding style • Pages lie flat • Editing capability with a machine	 1 19 PB Plastic Bind; Hole Size: 8 x 2.9 mm (0.313 x 0.116 in.) (L x W); Center-to-Center Hole Spacing: 14.3 mm (0.563 in.)	 Comb/Cerlox	 PB2600—TXC Quote
44-Hole ColorCoil • Professional and on trend • Pages lie flat with 360° rotation • Permanently binds • Keeps shape with bounce-back flexibility	 1 44 C4 Coil; Round; 4 Holes per inch; Hole Size: 4.4 mm (0.174 in.) Diameter; Center-to-Center Hole Spacing: 6.3 mm (0.2475 in.)	 Color Coil	 CI-12—TXC Quote
21-Hole WireBind • High-tech look • Pages lie flat with 360° rotation • Permanently binds	 1 21 W2 Wire; Rectangle; 2 Holes per inch, Hole Size: 6.4 x 5.4 mm; (0.250 x 0.214 in.) (L x W); Center-to-Center Hole Spacing: 12.7 mm (0.500 in.)	 WireBind	 TL2900—TXC Quote
32-Hole WireBind • High-tech look • Pages lie flat with 360° rotation • Permanently binds	 1 32 W3 Wire; Square; 3 Holes per inch, Hole Size: 4 x 4 mm; (0.156 x 0.156 in.) (L x W); Center-to-Center Hole Spacing: 8.5 mm (0.333 in.)	 Twin Loop Wire	 TL2900—TXC Quote
11-Hole VeloBind • Most secure style—permanently binds documents • Book-like finish • Great for filing, mailing	 1 11 VB Velobind; Round; 1 Hole per inch; Hole Size: 3.2 mm (0.125 in.) Diameter; Center-to-Center Hole Spacing: 25.4 mm (1 in.)	 VeloBind	 System 4 Bind—TXC Quote
32-Hole ProClick • Professional, upscale look • Fast and easy • Pages lie flat with 360° rotation • Zips and unzips for quick edits	 1 32 W3 ProClick; Rectangle; Hole Size: 4.9 x 5.5 mm; (0.196 x 0.215 in.) (L x W); Center-to-Center Hole Spacing: 8.5 mm (0.333 in.)	 ProClick	 Pronto P2000—TXC Quote
3-Hole 3 Ring	 1 3 3 Ring Binder; U.S. (Standard Looseleaf Patterns); Hole Size: 8 mm (0.316 in.) Diameter	 3-Hole 3 Ring	 3-Hole 3 Ring

Additional dies can be purchased from your local Xerox Supplies Representative or by calling 1-800-822-2200

Contact your Xerox representative for details and to find out more about our finishing options.